

Double-stick tape for the optics




It is double-stick tape for the optics based on silicone gel.

Features

(1) High visible light transmittance

(2)Transparency is high

Structure



Properties

Product name	Thickness (mm)	Peel Adhesion(N/inch) SUS	Total light tranmittance (%)	HAZE	Break strength N/10mm	Growth rate %	Shear force(N/inch ²) SUS
MGSi15	0.15	0.1	93.0	0.33	0.2	400	1
MGSi50	0.5	0.2	93.4	0.52	0.3	270	6

User is responsible for determining whether the KGK product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a KGK product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a KGK product. Given the variety of factors that can affect the use and performance of a KGK product to determine whether it is fit for a particular purpose and suitable for the user's method of application. KGK make no warranties on above data.

KGK Chemical Corporation. 940 Minaminagai Tokorozawa-City saitama-Pref 359-0011 Japan Tel: +81 4 2944 5151 Mail: info-k@kgk-tape.co.jp URL: https://www.kgk-tape.co.jp/

issue:2020/1