


# Cut aceMF (Blue)

**Feature** It is flexible, it does not stretch, it is a tape that can be handled straight.

**Use** Waterproof airtight, paint masking, curing, for binding

**Construction**



**Characteristic**

Outstanding handwork (excellent with scissors)

There is little adhesive residue.

There is little contamination on the adherend.

Polyethylene base material and acrylic adhesive are used and harmful gas is not generated even if incinerated.

Toluene is not used as the adhesive.

product name	Adhesive force N/25mm			color
	SUS	Veneer	PE	
Cut ace MF	7.5	5.0	4.5	Blue

**quantity**

Item name	size(mm)	quantity/box
Cut ace MF	50x25	30R

**Precautions on use**

● All technical data are prepared based on tests and measured values conducted at the laboratory of Joint Giken Kagaku Co., Ltd. However, product characteristics may vary greatly depending on environment and adherend. Therefore, regarding these characteristic data, it is a reference value, not a guaranteed value. Before using it please make sure that this product is suitable for the intended use and environment.

**Caution on storage**

● Please be sure to put it in a box and keep it.  
 ● Characteristic deterioration may occur depending on storage conditions.  
 ● Please choose a cold and dark place not to be exposed to direct sunlight for the storage location.  
 In particular, please do not expose to high temperature and high humidity (temperature 30 °C or more and humidity 50% or more forbidden).